

LED
no
compromise

10 Year
Warranty

60598
AS/NZS

IP4X

COI
compliant

Application

Viline delivers visual comfort through linear lighting. Homogenous microprism diffuser provides low glare lighting for workplaces, education & healthcare facilities over workstations or down long corridors.

Installation

Designed for recess in standard T-Rail ceilings, 1200mm and 600mm lengths to configure with ceiling. 100mm wide requires additional T-rail to be installed with fixture.

Design


End-to-end mounting recessed in T-rail creates effective linear lighting. Only 100mm wide provides the linear effect and 1200 or 600 modules provide flexibility in layout and design.

Sustainability

Designed for long life with Tridonic/Philips/Osram remote driver for easy replacement. Easily reused with new components and recycled at end of life.

Specification Data

Colour Temperature	4000K
Colour Rendering	95Ra, R9>80
Weight	1200mm 1.2kg, 600mm 0.7kg
LED Lifetime	L95 @50,000h
Driver Lifetime	100,000h
Cyanosis (COI)	0.156 (<3.3)
Flicker	PSTLM <1.0 SVM <0.4
M/P Ratio m-EER (WELLS)	0.8
M/P Ratio m-DER (CIE S 0-26)	0.72
SDCM	3-Step MacAdam



Product Selector

Code	DALI	Casambi	Size (mm)	Lumens	(mA)	Wattage	(lm/W)	Application Notes
VL12111	/DD	/CA	1200	1100	300	11	100	MH 2.4m, End to End Mounting Circulation Space, Workplace, Healthcare, Education
VL12113	/DD	/CA	1200	1300	375	13	100	MH 2.7m, End to End Mounting Circulation Space, Workplace, Healthcare, Education
VL12118	/DD	/CA	1200	1800	550	18	100	MH 2.7m, End to End Mounting Workplace, Healthcare, Education
VL12127	/DD	/CA	1200	2700	800	26	103	MH 3.0m, End to End Mounting Workplace, Healthcare, Education
VL06155	/DD	/CA	600	550	150	6	91	MH 2.4m, End to End Mounting Circulation Space, Workplace, Healthcare, Education
VL06165	/DD	/CA	600	700	200	7	100	MH 2.7m, End to End Mounting Circulation Space, Workplace, Healthcare, Education
VL06190	/DD	/CA	600	900	250	9	100	MH 2.7m, End to End Mounting Workplace, Healthcare, Education
VL06113	/DD	/CA	600	1400	400	15	93	MH 3.0m, End to End Mounting Workplace, Healthcare, Education

Accessories

Custom Options

SkyBlue® Tunable Spectrum 27 - 40K m-EER 0.47 - 0.92 | m-DER 0.42 - 0.83

SkyBlue® Tunable Spectrum 27 - 35K m-EER 0.47 - 0.83 | m-DER 0.42 - 0.75

CCT, Colour, Output Custom Widths - 150mm & 200mm

Red List Free - Living Building Challenge

