



# Planado Lite

579208.4040.2120.76-CRI90 | Linear luminaires



Surface-mounted luminaires  
LED  
L 1195, B 171, H 63



Comes with seismic safety bracket for diffuser

Linear luminaire with timeless functional design. Ideal for schools, corridors, waiting areas, nursing homes, patient rooms.  
Diffuser: plastic (polycarbonate), opal. Homogeneous and smooth light distribution. Screwless design on back side with better looking, large lighting area with high lumen efficiency. Quick and easy to install. 2 central cable inlets for looping the cable. Comes with seismic safety bracket for diffuser. Converter integrated.

## Lighting technology

Colour temperature	4.000 K
Rated luminous flux	4.350 lm
Beam angle	120°

## Electrical

Control gear	DALI
Voltage	220 - 240 V / 0 Hz, 50 - 60 Hz
System power	40 W
Luminaire efficacy	109 lm/W

## Approbations

Type of Protection	IP 44
Protection Class	I
Glow Wire Test	750°C
Impact Protection	IK06
Ambient temperature min.	-20 °C
Ambient temperature max.	45 °C
Trade mark	RoHS, CE

## Colour

Colour	white
--------	-------

## Dimensions

Length L	1.195 mm
Width B	171 mm
Height H	63 mm
Weight	2,88 kg

## Lamp

Lamp	LED
Colour temperature lamp	4000K
Colour rendering index (CRI)	90
Lifetime of lamp	50000 h