



Calido Clickbeam Mini

742129.003.75MAL | Surface mounted projector

Surface mounted projectors
4051859364337
LED
D 50, H 132



LED surface-mounted projector with modern cylindrical design with no visible cooling ribs. Housing: extruded aluminium profile, powder-coated. Cover and lever arm made of plastic. Rotation range: 356°. Swivel range: 90°. Heat resistant plastic ring black. Hybrid optical system with polycarbonate lens and reflector in faceted aluminium for particularly homogeneous lighting. Special Click Beam lens suitable for different beam angles. Adjustable lens position by means of push mechanism to adjust the beam angle. Black front ring to prevent glare from the side UVA- and IR-free light. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling. Converter integrated in the luminaire housing. The following accessories can be mounted without use of tools: honeycomb louvre.

Colour

Colour deep black, matt (RAL 9005)

Dimensions

Diameter D 50 mm
Height H 132 mm
Weight 180 g

Lamp

Lamp LED
Colour temperature 2800K
Colour rendering index (CRI) 80
Colour consistency (McAdam) 3
Lifetime 25000 h (L70/B50)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 2.800 K
Rated luminous flux 1.000 lm
Glare evaluation UGR (4H 8H) 1 18,5
Beam angle 21°
Colour temperature 2 2.800 K
Rated luminous flux 2 1.150 lm
Glare evaluation UGR (4H 8H) 2 20
Beam angle 2 34°

Electrical

Control gear Converter
Voltage 220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse 11
Luminaires on B16A fuse 18
Luminaires on C10A fuse 22
Luminaires on C16A fuse 36
Inrush current / inrush current duration 4.38 A / 24 µs
System power 12 W
Luminaire efficacy 84 lm/W
System power 2 12 W
Luminaire efficacy 2 96 lm/W

Approbations

Type of Protection IP 20
Protection Class II
Impact Protection IK03 (0,35 Joule)
Safety marks F-mark
ULOR 0
Trade mark CE
CIE Flux Code / CEN Flux Code 94 99 100 100 100
Energy efficiency class LED A++
Energy class of included lamp A++

Calido Clickbeam Mini

742129.003 | Surface mounted projector



Accessories

982448.003

Anti-glare honeycomb louvre
D 47, H 4
Honeycomb anti-dazzle-screen for
Calido Mini