

901625.002.76



Series: Sonis EVO Ceiling luminaires


Type of Installation: Ceiling mounting, Wall (surface)
 Type of Protection: IP 20
 Protection Class: I
 Lamp: LED
 Dimensions: L 602, B 602, H 47
 Colour: white



Housing and cover made of white powder-coated sheet steel, Alea Optical System: Reflector structure (ABS, aluminium vapour-plated, highly polished) with diffuser made of non-yellowing plastic (PMMA) opal for glare-free light at the workstation (screen-compliant according to EN 12464-1). Converter included. Lamp (LED) included.

Electro-technics:

Electric Gear	DALI
Voltage	220 - 240 V / 0 Hz, 50 Hz, 60 Hz
System Power	30 W
Number of fittings B10A	15
Number of fittings B16A	24
Number of fittings C10A	24
Number of fittings C16A	40



Testings:

Type of Protection	IP 20
Protection Class	I
Glow Wire Test	600°C - 30 seconds
Impact Protection	IK03 (0,35 Joule)
Safety Marks	F-mark
Other Marks	WEEE mark
Country Code	CE
Energy Efficiency Class LED	A+
Energy Efficiency Class of included lamp	A+

Lamp 1:

Number of Lamps	1
Lamp	LED
Socket	without socket
Light colour	830
Colour Temperature	3000K
Lifespan	50000 h (L80/B10)

Weights and measures:

Length L	602 mm
Width B	602 mm
Height H	47 mm
Suspension Length	
Ceiling Thickness	
Weight	4,97 kg

Lighting technology:

UGR	18,3
Luminaire Beam Angle	78°/74°
Luminaire flux	3.300 lm
Colour Rendering Index (CRI)	80