

# 451178.009




Series: Planox ECO Ceiling and wall luminaires

Type of Installation: Ceiling mounting, Wall (surface)  
Type of Protection: **IP 66**  
Protection Class: II  
Lamp: LED  
Dimensions: L 1350, B 67, H 56  
Colour: grey

Side panels: grey plastic, polycarbonate. Diffuser: opal plastic, polycarbonate. Converter: encapsulated, integrated and permanently connected to the diffuser and side panel. Cable screw fittings for convenient wiring. Quarter turn lock on both sides for simple installation Luminaire with integrated through wiring for lining up further (safety class II) luminaires. Ceiling mounting bracket made of stainless steel and triangular bracket for pendant mounting included in the scope of delivery. LED included.

## Electro-technics:

Electric Gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
System Power	41 W
Number of fittings B10A	4
Number of fittings B16A	6
Number of fittings C10A	8
Number of fittings C16A	13



## Testings:

Type of Protection	<b>IP 66</b>
Protection Class	II
Glow Wire Test	850°C - 30 seconds
Impact Protection	IK08 (5 Joule)
Safety Marks	D-mark
Other Marks	WEEE mark
Country Code	CE
Energy Efficiency Class LED	A+
Energy Efficiency Class of included lamp	A+

## Lamp 1:



Socket	without socket
Light colour	840
Number of Lamps	1
Lamp	LED
Colour Temperature	4000K
Lifespan	50000 h

## Weights and measures:

Length L	1.350 mm
Width B	67 mm
Height H	56 mm
Ceiling Thickness	
Weight	1,08 kg

## Lighting technology:

UGR	24,6
Luminaire Beam Angle	160°/104°
Luminaire flux	4.900 lm
Colour Rendering Index (CRI)	85



# 451178.009



Series: Planox ECO Ceiling and wall luminaires

Type of Installation: Ceiling mounting, Wall (surface)

Type of Protection: **IP 66**

Protection Class: II

Lamp: LED

Dimensions: L 1350, B 67, H 56

Colour: grey

Side panels: grey plastic, polycarbonate. Diffuser: opal plastic, polycarbonate. Converter: encapsulated, integrated and permanently connected to the diffuser and side panel. Cable screw fittings for convenient wiring. Quarter turn lock on both sides for simple installation Luminaire with integrated through wiring for lining up further (safety class II) luminaires. Ceiling mounting bracket made of stainless steel and triangular bracket for pendant mounting included in the scope of delivery. LED included.

## Accessories

### End piece for turn lock fastener with D 25 mm

982179.009	D 25, H 13	Blindstopfen D 47,5 mm für Drehverschluss grey
------------	------------	--

### Mounting brackets made of stainless steel (theft protection) for ceiling and wall mounting

982180.000		Wandbefestigung stainless steel
------------	--	---------------------------------

### Turn lock fastening

982186.009	D 48, H 50	Drehverschluss D 47,5 mm grey
------------	------------	-------------------------------