



Type of Installation: Ceiling mounting, Wall (surface)
 Type of Protection: **IP 66**
 Protection Class: II
 Lamp: LED
 Dimensions: L 1650, B 88, H 63
 Colour: white

Side panels plastic (polycarbonate) white. Diffuser: plastic(polycarbonate), opal. Converter encapsulated, integrated and permanently connected to the diffuser and side panel. Comfortable cable entry by means of cable gland and easy installation by turn lock fastener on both sides. Luminaire with integrated through-wiring for lining up further luminaires (incl. safety class I luminaires). Ceiling mounting bracket made of stainless steel and triangular bracket for pendant mounting included in the scope of delivery. Lamp (LED) included.

Electro-technics:

Electric Gear	DALI
Voltage	220 - 240 V / 0 Hz, 50 - 60 Hz
System Power	54 W
Number of fittings B10A	15
Number of fittings B16A	24

Testings:

Type of Protection	IP 66
Protection Class	II
Glow Wire Test	850°C - 30 seconds
Impact Protection	IK08 (5 Joule)
Safety Marks	D-mark
Other Marks	WEEE mark
Country Code	CE
Energy Efficiency Class LED	A+
Energy Efficiency Class of included lamp	A+

Lamp 1:

Light colour	840
Socket	without socket
Colour Temperature	4000K
Number of Lamps	1
Lamp	LED
Lifespan	50000 h

Weights and measures:

Length L	1.650 mm
Width B	88 mm
Height H	63 mm
Ceiling Thickness	
Weight	2,28 kg

Lighting technology:

UGR	24,1
Luminaire Beam Angle	131°/114°
Luminaire flux	7.150 lm
Colour Rendering Index (CRI)	80

