



# 901527.002.1.76



Series: Ledona Round IP65 Recessed downlights

Type of Installation: Recessed ceiling mounting  
 Type of Protection: **IP 65**  
 Protection Class: II  
 Lamp: LED  
 Dimensions: D 180, H 3  
 Colour: white


Recessed ring, luminaire housing and heat sink: die cast aluminium, powder coated. Faceted reflector: parabolic four-segment design, frosted aluminium, with highly polished light mixing chamber, transparent safety glass. Ceiling mount: spring system.

## Electro-technics:

Electric Gear	DALI
System Power	26 W
Voltage	220 - 240 V / 0 Hz, 50 - 60 Hz
Number of fittings B10A	45
Number of fittings B16A	80

## Testings:

Type of Protection	<b>IP 65</b>
Protection Class	II
Glow Wire Test	850°C - 30 seconds
Impact Protection	IK07 (2 Joule)
Safety Marks	Ball impact proof in accordance with DIN 18032-03, F-mark
Other Marks	WEEE mark
Country Code	CE
Energy Efficiency Class LED	A++
Energy Efficiency Class of included lamp	A++



## Lamp 1:

Number of Lamps	1
Socket	without socket
Colour Temperature	4000K
Lamp	LED
Light colour	840
Lifespan	50000 h (L90/B10)

## Weights and measures:

Diameter D	180 mm
Height H	3 mm
Ceiling cut-out	DA 160 mm
Recess Depth HE	92 mm
Ceiling Thickness	1-20 mm
Dimensions	L 178 x B 92 x H 30 mm
Weight	1,21 kg

## Lighting technology:

UGR	20,1
Luminaire Beam Angle	64°
Luminaire flux	2.750 lm
Colour Rendering Index (CRI)	85