



# 581632.0031.1

Series: Brick® EVO Wall luminaires

Type of Installation: Wall (surface)  
 Type of Protection: **IP 65**  
 Protection Class: I  
 Lamp: LED  
 Dimensions: L 120, B 120, H 24  
 Colour: anthracite metallic

Housing made of corrosion-resistant pressure die-cast Aluminium for outdoor use, powder coated. Drill hole deviations can be compensated. Integral driver. Toughened glass cover. LED choice of light colour 830 or 840. Terminal for 3 x 1 x 1,5mm<sup>2</sup>, max cable Ø 13mm.



### Electro-technics:

Electric Gear	Converter
System Power	4 W
Voltage	220 - 240 V / 50 - 60 Hz
Number of fittings B10A	30
Number of fittings B16A	40

### Testings:

Type of Protection	<b>IP 65</b>
Protection Class	I
Glow Wire Test	960°C - 30 seconds
Impact Protection	IK09 (10 Joule)
Safety Marks	F-mark
Other Marks	WEEE mark
Country Code	CE
Energy Efficiency Class LED	A+
Energy Efficiency Class of included lamp	A+

### Lamp 1:

Number of Lamps	1
Lamp	LED
Socket	without socket
Light colour	840
Colour Temperature	4000K
Lifespan	50000 h (L80/B10)

### Weights and measures:

Length L	120 mm
Width B	120 mm
Height H	24 mm
Weight	40g

### Lighting technology:

UGR	29
Luminaire Beam Angle	
Luminaire flux	60 lm
Colour Rendering Index (CRI)	80

