

581604.0031

Series: Rounded® superflach Wall luminaires

Type of Installation: Wall (surface)
 Type of Protection: **IP 66**
 Protection Class: I
 Lamp: LED
 Dimensions: D 268, H 96
 Colour: anthracite metallic

Pressure die-cast housing of corrosion resistant Aluminium, powder coated, spherical cap diffuser of opal polycarbonate with fixing clamps, drill hole deviations can be compensated, second cable entry for loop-through.

Electro-technics:

Electric Gear without converter
 Voltage 220 - 240 V / 50 Hz
 System Power 8,5 W

Testings:

Type of Protection **IP 66**
 Protection Class I
 Glow Wire Test 850°C - 30 seconds
 Impact Protection IK10 (20 Joule)
 Safety Marks F-mark
 Other Marks WEEE mark
 Country Code CE
 Energy Efficiency Class LED A+
 Energy Efficiency Class of included lamp A+

Lamp 1:


Light colour 840
 Number of Lamps 1
 Lamp LED
 Socket without socket
 Colour Temperature 4000K
 Lifespan 45000 h (L70/B50)

Weights and measures:

Diameter D 268 mm
 Height H 96 mm
 Weight 1,65 kg

Lighting technology:

UGR 24,6
 Luminaire Beam Angle
 Luminaire flux 250 lm
 Colour Rendering Index (CRI) 80



Replacement parts

Replacement diffusers

Replacement parts

08-581019.012 D 226, H 60