


**80289.000** White (RAL9016)  
 LED 8W 1100lm 4000K neutral white  
 DALI  
 Version 3  
 Covered mounting detail  
 Lens system, wide flood

**Product description**  
 Housing: cast aluminium, designed as heat sink, with connection cable L 500mm. Fixing springs for ceiling thicknesses of 1-25mm. Includes ERCO DALI control gear. 4-pole terminal block.  
 LED module: high-power LEDs on metal-core PCB. Lens system made of optical polymer.  
 Anti-glare cone with covered mounting detail: polymer, white (RAL9016). Optical cut-off 30°.  
 The luminaire is splash water-protected on the room side.  
 Dimming possible via commercially available push-buttons (Push Dim).  
 Protection Class II  
 Weight 0.49kg  
 Version with 2700K CRI>=90 or 4000K CRI>=90 available on request.



Beam angle  
 C<sub>0</sub> 70°

**Technical data**

Luminous flux of the luminaire	993lm
Connected load	11W
Luminaire efficacy	90lm/W
Colour deviation	2 SDCM
Colour rendition index	CRI ≥80
Lumen maintenance (LM-80/TM-21)	L90/B10 ≤50000h
Lumen maintenance (LED manufacturer specifications)	L90 ≤100000h
LED failure rate	0.1% ≤50000h
Dimming range	0.1%-100%
Dimming method	CCR
LMF	E
Energy efficiency class	EEI A++
Standby power per control gear	0.4W
Luminaires per circuit breaker B16	260

For your regional contact in the ERCO  
 Sales network click here  
[www.erco.com/contact](http://www.erco.com/contact)

Technical Region: 220V-240V/50Hz  
 We reserve the right to make technical and design changes.  
 Edition: 29.03.2018  
 Current version under  
[www.erco.com/80289.000](http://www.erco.com/80289.000)

## Planning data

80289.000	LED 8W 1100lm 4000K neutral white
Connected load	P: 11 W
Connected load per 100lx	P*: 1.0 W/m <sup>2</sup>
Number of luminaires per 100lx	n*: 9.3 1/100m <sup>2</sup>

80289.000	LED 8W 1100lm 4000K neutral white
Number of luminaires per 100m <sup>2</sup> for	100lx    200lx    300lx    500lx
	10        19        28        47

80289.000	LED 8W 1100lm 4000K neutral white
Module (m)	1.2x1.8    1.8x1.8    1.8x2.4    2.4x2.4
Illuminance E <sub>n</sub> (lx) for module (m)	498        332        249        187

### Correction table

Ceiling	0.70	0.70	0.70	0.50	0
Wall	0.70	0.50	0.20	0.20	0
Floor	0.50	0.20	0.20	0.10	0

k	0.6	85	61	65	59	54
k	1.0	98	76	79	72	67
k	1.5	107	89	90	83	78
k	2.5	113	100	97	90	84
k	3.0	115	104	100	93	86

Cleaning (a)	1				2				3			
Ambient conditions	P	C	N	D	P	C	N	D	P	C	N	D
LMF	0.96	0.94	0.90	0.86	0.93	0.91	0.86	0.81	0.92	0.90	0.84	0.79
RSMF	0.97	0.95	0.91	0.86	0.97	0.94	0.90	0.86	0.97	0.94	0.90	0.86

Hours of operation (h)	1000	5000	10000	20000	30000	40000	50000
LLMF	1.00	0.99	0.98	0.96	0.94	0.92	0.90
LSF	1	1	1	1	1	1	1

- MF LMFxRSMFxLLMFxLSF
- MF Maintenance Factor
- LMF Luminaire Maintenance Factor
- RSMF Room Surface Maintenance Factor
- LLMF Lamp Lumens Maintenance Factor
- LSF Lamp Survival Factor
- P Room pure
- C Room clean
- N Room normal
- D Room dirty

### Technical data in accordance with international norms and standards


IEC 60598	Luminaires – Part 1+2: general requirements, specific requirements and tests
IEC 62031	LED modules for general lighting – safety requirements
IEC 62471	Photobiological safety of lamps and lamp systems
EN13032-4	Light and lighting – measurement and representation of photometric data
CIE 13	Method of measuring and specifying colour rendering properties of light sources

All technical data is subject to industrially standard tolerances.  
Also see [www.erco.com/erco-led](http://www.erco.com/erco-led)

## Accessories



**83736.000**  
 Concrete housing  
 Stainless steel, galvanised/powder-coated.  
 Recommended 0-8mm aggregate for the concrete.  
 Weight 3.35kg



**88290.000**  
 Compensation set  
 For over-large ceiling aperture.  
 Lock ring: steel sheet, galvanised.  
 Mounting for ceiling thicknesses of 15-25mm.  
 Cover ring: metal, white.  
 When ordering state ceiling aperture of the luminaire and diameter of the available ceiling aperture.



**83980.000**  
 Cover ring  
 Metal, white. For covering the gap where ceiling cut-outs are too big. Inner and outer diameter to be specified when placing order.