


# EVALA 300



LED  
no  
compromise

10 Year  
Warranty

60598  
AS/NZS

IP50

COI  
compliant

## Application

Low temperature, long life, sustainable light fixture designed for use at variable mounting heights in workplace, education, healthcare and community projects.

## Installation

Flexibility of installation for recess in T-rail, plaster ceilings, surface mount or wire suspension.

## Design


Homogenous microprism diffuser with excellent glare control, made in New Zealand.

## Sustainability

Designed for long life with Tridonic/Philips/Osram remote driver for easy replacement. Easily reused with new components and recycled at end of life.

## Specification Data

Colour Temperature	4000K
Colour Rendering	95Ra, R9>80
Weight	1200mm 3.8kg, 600mm 2.2kg
LED Lifetime	L95 @50,000h
Driver Lifetime	100,000h
Cyanosis (COI)	0.171 (<3.3)
Flicker	PSTLM <1.0   SVM <0.4
M/P Ratio m-EER (WELLS)	0.81
M/P Ratio m-DER (CIE S 0-26)	0.73
SDCM	3-Step MacAdam



## Product Selector

Code	DALI	Casambi	Size (mm)	Lumens	(mA)	Wattage	(lm/W)	Application Notes
EV12326	/DD	/CA	1200x300	2600	700	23	115	MH 2.7m, 2.4x2.4m - Green Star Optimised, Workplace, Education, Healthcare
EV12330	/DD	/CA	1200x300	3000	800	26	115	MH 2.7 - 3.0m, 2.4x2.7m - Workplace, Education, Healthcare
EV12333	/DD	/CA	1200x300	3300	900	29	114	MH 3.0 - 4.0m, 2.4x2.7m - Workplace, Education, Healthcare
EV12350	/DD	/CA	1200x300	5000	1350	45	110	MH >4.0m High Output - Retail, Detail work, Examination, Propose Dimming
EV06313	/DD	/CA	600x300	1300	325	12	104	MH 2.7m - Green Star Optimised, Workplace, Education, Healthcare
EV06315	/DD	/CA	600x300	1500	375	14	106	MH 2.7 - 3.0m - Workplace, Education, Healthcare
EV06317	/DD	/CA	600x300	1700	450	16	107	MH 3.0 - 4.0m - Workplace, Education, Healthcare
EV06325	/DD	/CA	600x300	2500	675	23	109	MH >4.0m High Output - Retail, Detail work, Examination, Propose Dimming

## Accessories

Plaster Kit
Surface Mount Kit
Suspension Kit
Seismic Wire Kit

## Custom Options

SkyBlue® Tunable Spectrum 27 - 40K	m-EER 0.47 - 0.92   m-DER 0.42 - 0.83
SkyBlue® Tunable Spectrum 27 - 35K	m-EER 0.47 - 0.83   m-DER 0.42 - 0.74
CCT, Colour, Output	
Red list free - Living Building Challenge	

