



Installation

Luminaire designed for recessed installation where protection from unauthorised access is priority. Includes backing plate to topside of ceiling and Tamper proof screws as standard. Luminaire must not be covered with insulation and 100mm clearance from other elements must be maintained.

Connection

Luminaire supplied with halogen free flexes installer must ensure flexes are kept away from luminaire heatsink.

Design

Designed for use in inpatient health facilities with an aesthetic designed to replicate lighting in a residential environment, luminaire body is white powdercoat, custom colours available on request.

Order Codes

Description	Code	Control	CCT*	CRI*	Lumens*	Wattage*
Salvalux - Large - 3000K - White	SAL-L-3-WH	DALI	3000K	80Ra	2546lm	43.3
Salvalux - Large - 3000K - White + Amber NL	SAL-L-3-WH-AMB	DALI	3000K	80Ra	2546lm	43.3
Salvalux - Large - 3000K - White + Amber NL + RGB	SAL-L-3-WH-AMB-RGB	DALI	3000K	80Ra	2546lm	43.3

*White light only, + Amber 2.5W, + RGB 10.2W

Custom Options (consult Energylight)

- Custom colour
- Casambi
- BIOS

Lifetime

- White L80 @ 53000h
- Amber L90 > 60000h
- RGB L70 > 50000h

