



LED
no
compromise

10 Year
Warranty

60598
AS/NZS

IP4X

UGR<19

Application

VIFO represents visual comfort for office. A smooth transition of brightness through a unique dual diffuser design provides a smooth transition from the central light chamber to ceiling. Control of luminance above 65° provides for UGR19 compliance for all lumen output options a perfect fit for office lighting.

Installation

Designed for recess in T-rail ceilings as standard or plaster ceiling with optional kit.

Design


Lumen outputs tailored for workplace, designed and manufactured in New Zealand.

Sustainability

Highly efficient with low temperature LED's and aluminium body, provide for a long life, easily re-used or recycled at the end of life.

Specification Data

Colour Temperature	4000K
Colour Rendering	95Ra, R9>80
Weight	3.7kg
LED Lifetime	L95 @50,000h
Driver Lifetime	100,000h
Cyanosis (COI)	0.212 (<3.3)
Flicker	PSTLM <1.0 SVM <0.4
M/P Ratio m-EER (WELLS)	0.79
M/P Ratio m-DER (CIE S 0-26)	0.72
SDCM	3-Step MacAdam



Product Selector

Code	DALI	Casambi	Size (mm)	Lumens	(mA)	Wattage	(lm/W)	Application Notes
VF06626	/DD	/CA	600x600	2600	650	22	118	MH 2.7m, 2.4x2.4m Green Star Optimised, Workplace, Education, Healthcare
VF06629	/DD	/CA	600x600	2900	750	25	116	MH 2.7-3.0m, 2.4x3.0m Workplace, Education, Healthcare
VF06633	/DD	/CA	600x600	3300	850	29	113	MH 3.0-4.0m, 3.0x3.0m Workplace, Education, Healthcare

Accessories

Plaster Kit

Custom Options


SkyBlue® Tunable Spectrum 27 - 40K m-EER 0.47 - 0.92 | m-DER 0.42 - 0.83

SkyBlue® Tunable Spectrum 27 - 35K m-EER 0.47 - 0.83 | m-DER 0.42 - 0.74

CCT, Colour, Output

Red list free - Living Building Challenge





DIMENSIONS

595x595mm

WEIGHT

3.7kg

COLOUR TEMPERATURE

4000K

COLOUR RENDERING

95Ra, R9>80

DIRECT OUTPUT

2600-3300lm

LED LIFETIME

L95 @50,000h

DRIVER LIFETIME

100,000h

WEIGHT AND COMPOSITION BY MATERIAL

Material	Weight (g)	Weight (%)	GWP (kgCO ₂ e)
NZ ALUMINIUM	149.6	5.2	1.04
GLOBAL ALUMINIUM	1145.8	39.5	15.01
COPPER	11.6	0.4	0.04
PLASTICS	741.5	25.6	4.85
STEEL	36.3	1.3	0.11
ELECTRONIC COMPONENTS	331.2	11.4	13.05
CARD	486.0	16.7	0.90

Note: LED driver has been excluded. Driver EPD provided on request.

RESULTS

TM65 Calculation		
ASSESSMENT PARAMETER		GLOBAL WARMING POTENTIAL (GWP)
UNIT	-	[kg CO ₂ eq]
PRODUCTION	A1–A4	47.1
REPAIR	B3	1.09
END-OF-LIFE	C2–C4	0.447
TOTAL (x1.3 BUFFER)	A1–C4	48.6

TM65ANZ SUMMARY

TM65ANZ is an engineering standard published by the Chartered Institution of Building Services Engineers (CIBSE). It provides a clear and concise framework to estimate the embodied carbon of a product when environmental product declarations (EPD's) are not available. In order to appropriately use a TM65ANZ calculation it is important to understand the scope of the method.

Originally created in the United Kingdom, TM65ANZ is a branch of the TM65 standard for Australasian application. It provides additional assumptions that can be made to make the calculation process easier.

WHAT TM65ANZ IS

- A method for estimating the embodied carbon of building services equipment
- A first step to promoting transparency in the industry
- A reporting methodology
- A set of rules that allows the production of comparable metrics
- A simple, replicable methodology


WHAT TM65ANZ IS NOT

- A detailed and holistic assessment of a product's environmental impacts
- An environmental product declaration (EPD)
- A peer-reviewed certification
- An exhaustive assessment of a product's materials
- A detailed life cycle assessment of building services at a system level

CALCULATION PROCESS

The calculation process is broken up into four main sections. Depending on the availability of information on the product, different levels of the TM65ANZ process can be undertaken including a 'basic' and 'mid-level' calculation. For this report a 'mid-level' calculation was done.

STAGES OF CALCULATION



All sections written in green text are included in a mid-level calculation

ASSUMPTIONS

The calculation for 'Transport to Site' was made based on land freight from Christchurch to Auckland.