

VIFO 600



LED
no
compromise

10 Year
Warranty

60598
AS/NZS

IP4X

UGR<19

Application

VIFO represents visual comfort for office. A smooth transition of brightness through a unique dual diffuser design provides a smooth transition from the central light chamber to ceiling. Control of luminance above 65° provides for UGR19 compliance for all lumen output options a perfect fit for office lighting.

Installation

Designed for recess in T-rail ceilings as standard or plaster ceiling with optional kit.

Design


Lumen outputs tailored for workplace, designed and manufactured in New Zealand.

Sustainability

Highly efficient with low temperature LED's and aluminium body, provide for a long life, easily re-used or recycled at the end of life.

Specification Data

Colour Temperature	4000K
Colour Rendering	95Ra, R9>80
Weight	3.7kg
LED Lifetime	L95 @50,000h
Driver Lifetime	100,000h
Cyanosis (COI)	0.212 (<3.3)
Flicker	PSTLM <1.0 SVM <0.4
M/P Ratio m-EER (WELLS)	0.79
M/P Ratio m-DER (CIE S 0-26)	0.72
SDCM	3-Step MacAdam



Product Selector

Code	DALI	Casambi	Size (mm)	Lumens	(mA)	Wattage	(lm/W)	Application Notes
VF06626	/DD	/CA	600x600	2600	650	22	118	MH 2.7m, 2.4x2.4m Green Star Optimised, Workplace, Education, Healthcare
VF06629	/DD	/CA	600x600	2900	750	25	116	MH 2.7-3.0m, 2.4x3.0m Workplace, Education, Healthcare
VF06633	/DD	/CA	600x600	3300	850	29	113	MH 3.0-4.0m, 3.0x3.0m Workplace, Education, Healthcare

Accessories

Plaster Kit

Custom Options

SkyBlue® Tunable Spectrum 27 - 40K m-EER 0.47 - 0.92 | m-DER 0.42 - 0.83

SkyBlue® Tunable Spectrum 27 - 35K m-EER 0.47 - 0.83 | m-DER 0.42 - 0.74

CCT, Colour, Output

Red list free - Living Building Challenge

