


Product data sheet

ARELO
901620.002.1
RZB



Series: Arelo Type of Protection: IP 44 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Bezel ring: die-cast aluminium, powder-coated. Housing made of plastic (UV-resistant polycarbonate). Aluminium faceted reflector, highly polished anodised finish. LED diffuser, satin finish (UV-resistant polycarbonate), shockproof. Spring fastening system. Passive cooling. Suitable for through-wiring. Electronic ballast included. <p/>LED included. Available Colours: white Type of Installation: Recessed ceiling mounting Dimensions: D 172, H 2 Lamp: LED Life time: 50000 h (L70/B50) Colour Temperature: 4000K Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK05 (0,70 Joule) Luminaire flux LED: 1950lm System power: 17W Beam Angle: 94° Number of fittings B10A: 11 Number of fittings B16A: 19 Number of fittings C10A: 23 Number of fittings C16A: 38 Inrush current: 4,17A Unified Glare Ratio: 23,9 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	80
Total flux	1950 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	17 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3 mm
Diameter: 172 mm

Adjustability

Fixed

Electric

System power: 17 W

Protection

IP: 44
IK: 05